

**POLYFLOC FLOCCULENT**

=====  
 Section 1 -- PRODUCT AND COMPANY IDENTIFICATION  
 -----

PRODUCT NAME	HMIS CODES	
POLYFLOC Flocculent	Health	2
PRODUCT CODES	Flammability	2
PFF/1, PFF/5 PFF/20	Reactivity	0
CHEMICAL FAMILY	PPI	B
Organic/Inorganic		
USE		
Water Treatment		
MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.	
Greenleaf Solutions Ltd	Poisons Information Centre	
PO Box 64-125	New Zealand 0800-764-766	
Botany, Auckland NZ 1703	Australia 13-1126	
DATE OF PREPARATION	TECHNICAL SERVICE TELEPHONE NO.	
15 <sup>th</sup> December, 2012	0064-9-272 4141	

=====  
 Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS  
 -----

ALUMINIUM SULFATE 20-30% CAS 10043-01-3

=====  
 Section 3 -- HAZARDS IDENTIFICATION 8.3A 6.3B  
 -----

SUMMARY OF ACUTE HAZARDS

Slightly corrosive. This product has the potential to cause adverse health effects with eye contact or prolonged skin contact. Aluminium sulphate hydrolyses to form sulphuric acid. Due to the low vapour pressure of this product an inhalation hazard is not anticipated with normal use. Use safe work practices to avoid direct eye or skin contact and vapour/ mist generation-inhalation.

Eye Corrosive - severe irritant. Exposure may result in pain, redness, corneal burns and ulceration with possible permanent damage with prolonged contact.

Inhalation Slightly corrosive - irritant. Over exposure at high levels may result in mucous membrane irritation of the nose and throat with coughing. Due to the low vapour pressure of this product an inhalation hazard is not anticipated.

Skin Slightly corrosive. Prolonged contact may result in irritation, skin rash, dermatitis, ulceration and burns.

Ingestion Slightly corrosive. Ingestion may result in ulceration to the mouth and throat with nausea and vomiting.

=====  
 Section 4 -- FIRST AID MEASURES  
 -----

Eye Flush gently with running water, holding eyelids open for 20 minute period. Seek immediate medical attention.

Inhalation Leave area of exposure immediately. If symptoms occur, seek urgent medical attention. If assisting a victim avoid becoming a casualty, wear a Full-face Type B (Inorganic and acid gas) respirator or Air-line respirator (in poorly ventilated areas). If victim is not breathing apply artificial respiration.

Skin Remove contaminated clothing and gently flush affected areas with water. Seek medical attention if irritation develops. Launder clothing before reuse.

Ingestion If poisoning occurs, contact a Doctor or Poisons Information Centre on 13 11 26 (Australia Wide). Do not induce vomiting. Give a glass of water to drink. Seek urgent medical attention.

=====  
Section 5 -- FIRE FIGHTING MEASURES  
-----

Non flammable. If product is present in a fire, toxic gases may be evolved. Evacuate area and contact emergency services. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use water fog to cool intact containers and nearby storage areas. Extinguishing Non flammable. Prevent contamination of drains or waterways, absorb runoff with sand or similar.

=====  
Section 6 -- ACCIDENTAL RELEASE MEASURES  
-----

Spillage For liquid spills: contact emergency services. Clear area of unprotected personnel. Ventilate area where possible. Wear PVC gloves, a Full-face Type B (Inorganic and acid gas) respirator or Air-line respirator, full-length PVC coveralls & boots. Cover with sodium bicarbonate or 50-50 mixture of sodium carbonate & calcium hydroxide. Collect for complete neutralisation & appropriate disposal.

=====  
Section 7 -- HANDLING AND STORAGE  
-----

Storage Store in secured, cool, dry, well ventilated area, removed from alkalis (e.g. sodium hydroxide), most metals and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate fire prevention and ventilation systems.

=====  
Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION  
-----

RESPIRATORY PROTECTION (SPECIFY TYPE): In confined, poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air respirators during soldering operations until fumes have dissipated.

VENTILATION - LOCAL EXHAUST: Acceptable

SPECIAL: Explosion proof

MECHANICAL (GENERAL): Acceptable

OTHER: N/A

PROTECTIVE GLOVES: Wear rubber gloves.

EYE PROTECTION: Safety glasses (ANSI Z-87.1 or equivalent)

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Chemical resistant coveralls

WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

=====  
 Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES  
 -----

Flammability: NON FLAMMABLE Flash Point: NOT RELEVANT  
 Boiling Point: NOT AVAILABLE Melting Point: NOT RELEVANT  
 Exposure Standard (TWA): 2 mg/m3 Aluminium dust Evaporation Rate: NOT AVAILABLE  
 pH: NOT AVAILABLE % Volatiles: NOT AVAILABLE  
 Specific Gravity: 1.3 Solubility: SOLUBLE  
 Vapour Pressure: NOT AVAILABLE Upper Explosion Limit: NOT RELEVANT  
 Lower Explosion Limit: NOT RELEVANT

=====  
 Section 10 -- STABILITY AND REACTIVITY  
 -----

STABILITY: Stable  
 CONDITIONS TO AVOID: None  
 INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizers, acids and bases.  
 HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO, and fragmented hydrocarbons.  
 HAZARDOUS POLYMERIZATION: Will not occur.

=====  
 Section 11 -- TOXICOLOGY INFORMATION  
 -----

CHRONIC HEALTH HAZARDS

Large discharges may contribute to the acidification of water and soil and will injure aquatic life and soil micro-organisms

TOXICOLOGY DATA  
 LD50 6207mg/kg (Oral-Mouse)

=====  
 Section 12 -- Ecological Information  
 -----

ECOLOGICAL DATA  
 Unlikely to cause harmful effects  
 Remains indefinitely in the environment as Hydroxide

=====  
 Section 13 -- DISPOSAL CONSIDERATIONS  
 -----

Wearing the protective equipment detailed above, neutralise to pH 6-8 by SLOW addition to a saturated sodium bicarbonate solution or similar basic solution. Dilute with excess water and flush to drain. Waste disposal should only be undertaken in a well ventilated area or using a fume cupboard. Do not add water to un-reacted acidic products.  
 Transport Not regulated for transport purposes.

=====  
 Section 14 -- TRANSPORTATION INFORMATION  
 -----

Transport Not regulated for transport purposes.

=====  
Section 15 -- REGULATORY INFORMATION  
-----

REGULATORY DATA

EEC Classification: Irritant Hazard Symbol Xi  
-----

=====  
Section 16 -- OTHER INFORMATION  
-----

The information contained in this safety data sheet is given in good faith. It is accurate to the best of our knowledge and belief and represents the most up to date information. The information given in this data sheet does not constitute or replace the users own assessment of workplace risk as required by other health and safety legislation.